



PENNZOIL ULTRA™ RACING 10W-60 FULL SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

PENNZOIL ULTRA™ RACING 10W-60 FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology™, from the maker of the leading motor oil in America, is an advanced proprietary synthetic formula designed to exceed the toughest car manufacturer standards and engineered to keep your engine closer to factory clean. Because at Pennzoil we know, a cleaner engine is better protected, more efficient and delivers optimum performance.

PENNZOIL ULTRA™ RACING 10W-60 FULL SYNTHETIC MOTOR OIL has been tried, tested and proven even under the most extreme driving conditions and is founded on Shell and Pennzoil technology and Formula 1 and NASCAR racetrack experience over many years.

PENNZOIL ULTRA™ RACING 10W-60 FULL SYNTHETIC MOTOR OIL is specially designed to provide ultimate engine performance and protection for race tuned engines.

APPLICATION

PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology™ [is specifically designed for the Ferrari 360 Modena Challenge, for sporty use of all standard Ferrari & Maserati cars, and for most race tuned engines.

FEATURES

- Hyper Cleansing Technology™
- Extremely low chlorine content

BENEFITS

- Seeks out and dissolves contaminants safely into the oil before they form deposits in the engine
- Helps to prevent the build-up of sludge, damaging deposits, corrosion and engine wear
- Provides oil stability and endurance under extreme conditions (heat, load and speed) for protection against viscosity and thermal breakdown
- Provides proven protection for critical engine parts
- Helps protect emissions systems

SPECIFICATIONS & APPROVALS

- Ferrari – Exclusive to Pennzoil Ultra™ in the USA
- Maserati
- BMW M
- VW 501.1 and VW 505.00
- MB 229.1
- Fiat 9.55535 H3
- Exceeds the requirements of ACEA A3/B3/B4
- Exceeds the requirements of API SM/CF and previous categories

HEALTH & SAFETY

Guidance on Health and safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your local Pennzoil representative.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



Technical Data Sheet

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES PENNZOIL ULTRA™ RACING 10W-60 FULL SYNTHETIC MOTOR OIL

TEST	METHOD	TYPICAL RESULTS
Viscosity Grade.	SAE J300	10W-60
API Service		SM/CF
ACEA		A3/B3/B4
Viscosity		
@ 40°C, cSt	ASTM D-445	151
@ 100°C, cSt	ASTM D-445	22.8
Flash Point, °F	ASTM D-93	215
Pour Point, °C	ASTM D-97	-39

These characteristics are typical. While future production will conform to Pennzoil® specifications, variations in these characteristics may occur. The information contained herein is subject to change without notification.